

FEATURED



Pan-Term® BSV18X-MY Butt Splice, Red, Vinyl, 18-22 AWG, PK1000

BSV18X-MY

Panduit BSV18X-MY Vinyl Insulated Butt Splice

Specifications

Product Type	Butt Splice
Base Material	Copper
Barrel Type	Funnel Entry
Finish/Coating	Tin-Plated
Copper Conductor Size (AWG)	22-18
Copper Code Conductor Size (AWG)	22-18
Maximum Copper Conductor Size (AWG SOL)	18
Maximum Copper Conductor Size (AWG STR)	18
Minimum Copper Conductor Size (AWG SOL)	22
Minimum Copper Conductor Size (AWG STR)	22
Maximum Metric Conductor Size (mm ²)	1
Minimum Metric Conductor Size (mm ²)	0.5
Insulation Material	Vinyl
Overall Length (In.)	1.03
Overall Length (mm)	26.2
Overall Width (In.)	0.17
Overall Width (mm)	4.3
Standards Met	UL 486C, CSA C22.2 No.65
UL Temperature Rating (°C)	105
UL Temperature Rating (°F)	221
CSA Temperature Rating (°C)	105
CSA Temperature Rating (°F)	221
Maximum Voltage (V)	600
Maximum Voltage (kV)	0.6
Color Code	Red
Wire Strip Length (In.)	5/16
Wire Strip Length (mm)	7.9

Specifications (continued)

Sub Brand	Pan-Term®
Part Features	• Expanded wire entry designed to accommodate wire with a larger insulation thickness • Designed to splice two solid or stranded wires together to repair or lengthen wires • Internal wire stop assures proper length of insertion into terminal barrel

Packaging Detail

UPC	07498340796
Std. Pkg. Qty.	1000
Std. Pkg. Volume (cf)	0.1031
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000