



QuickNet™ Trunk Cable Assembly

FWUYL7575KAM034

OM5, 24 Fiber Trunk, Low Smoke Zero Halogen, PanMPO Female to PanMPO Female, HD Flex Transition, Method A, Ultra Insertion Loss, with Pulling Eye on one end - 34 Meters

Specifications

Fiber Type	OM5
Number of Fibers	24
Sub Brand	QuickNet™
Flammability Rating	LSZH
Fiber Diameter (µm)	50
Overall Length (ft.)	111.55
Overall Length (m)	34
Fiber Polarity	Method A
Cable Color	Lime
Pulling Eye	Yes
Product Type	Trunk Cable Assembly
Standards Met	Meets or exceeds ISO/IEC 11801, TIA/EIA-568-C.3, TIA-604-5 (FOCIS-5), TIA/EIA-568-C.1, RoHS compliant, TIA-492-AAAD, IED 60793-2-10 type A1a.3
Application	Data centers requiring quick infrastructure deployment with extended reach. Small diameter trunk cable assemblies use 30 to 40% less space which is ideal for high density cable applications.

Packaging Detail

UPC	61305635230
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.9400
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000