

ThinkSystem Intel P5600 Mainstream NVMe PCIe 4.0 x4 SSDs

Product Guide (withdrawn product)

The Intel SSD D7-P5600 Series Mainstream NVMe SSDs are advanced data center SSDs optimized for mixed read-write performance, endurance, and strong data protection for Lenovo servers. With a PCIe 4.0 x4 interface, they are designed for greater performance and endurance in a cost-effective design, and to support a broader set of workloads.

The Intel P5600 SSDs are based on Intel-developed controller, firmware, and 96-layer TLC Intel 3D NAND technology. Rigorous qualification and compatibility testing by Lenovo ensures a highly reliable SSD.



Figure 1. ThinkSystem Intel P5600 Mainstream NVMe PCIe 4.0 x4 SSD (shown without the ThinkSystem hot-swap tray)

Did You Know?

The Intel D7-P5600 SSDs have a PCIe 4.0 (Gen 4) host interface, where sequential performance is doubled over the PCIe 3.0 host interface. The drives are also fully compatible with a PCIe 3.0 host interface providing optimal performance and enabling compatibility across server families.

NVMe (Non-Volatile Memory Express) is a technology that overcomes SAS/SATA SSD performance limitations by optimizing hardware and software to take full advantage of flash technology. Intel Xeon processors efficiently transfer data in fewer clock cycles with the NVMe optimized software stack compared to the legacy Advance Host Controller Interface (AHCI) stack, thereby reducing latency and overhead. These SSDs connect directly to the processor via the PCIe bus, further reducing latency and TCO.

Part number information

The following table lists the ordering part numbers and feature codes for the SSDs.

Withdrawn from marketing: All P5600 drives are now withdrawn from marketing.

Table 1. Ordering information

Part number	Feature	Description
2.5-inch hot-swap drives		
4XB7A17152	BCFV	ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD
4XB7A17153	BCFR	ThinkSystem 2.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD
4XB7A17154	BCFS	ThinkSystem 2.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD
3.5-inch hot-swap drives		
4XB7A17155	BCFM	ThinkSystem 3.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD
4XB7A17156	BCFJ	ThinkSystem 3.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD
4XB7A17157	BCFQ	ThinkSystem 3.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD
Trayless drives		
4XB7A71356	BFPN	ThinkSystem 2.5" 15mm U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD
4XB7A71357	BFPP	ThinkSystem 2.5" 15mm U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD

The part numbers for the drives include the following items:

- One drive with a hot-swap tray attached (hot-swap drives only)
- Publication flyer

Features

Non-Volatile Memory Express (NVMe) is PCIe high performance SSD technology that provides high I/O throughput and low latency. NVMe interfaces remove SAS/SATA bottlenecks and unleash all of the capabilities of contemporary NAND flash memory. Each NVMe PCI SSD has direct PCIe x4 connection, which provides at significantly greater bandwidth and lower latency than SATA/SAS-based SSD solutions. NVMe drives are also optimized for heavy multi-threaded workloads by using internal parallelism and many other improvements, such as enlarged I/O queues.

With a PCIe 4.0 host interface, the P5600 drives offer significant increase in maximum throughputs supported, from 3.2 GB/s for sequential reads with the P4610 drives to up to 7 GB/s with the P5600 drives, more than double the performance. Sequential writes also increase from 3.2 GB/s with the P4610 to up to 4.3 GB/s with the P5600 drives.

The Intel P5600 NVMe drives have the following key characteristics:

- PCIe 4.0 connection for each NVMe drive
- Also supports PCIe 3.0 host connection for servers with first and second-generation Intel Xeon Scalable processors or with PCIe 3.0 NVMe switch adapters
- Intel 96 layer TLC 3D NAND Flash Memory
- Ultra-low I/O latency, with a read latency as low as of 9 μ s and write latency as low as 12 μ s
- Suitable for mixed read-write workloads
- Available in capacities up to 6.4 TB

- Variable sector size and end-to-end data-path protection
- Enhanced power-loss data protection
- Thermal throttling and monitoring
- SMART health reporting

The key metric for solid state drives is their endurance (life expectancy). SSDs have a huge, but finite, number of program/erase (P/E) cycles, which determines how long the drives can perform write operations and thus their life expectancy. Performance SSDs have better endurance than Mainstream SSDs, which in turn have better endurance than Entry SSDs.

SSD write endurance is typically measured by the number of program/erase cycles that the drive can incur over its lifetime, which is listed as TBW in the device specification. The TBW value that is assigned to a solid-state device is the total bytes of written data that a drive can be guaranteed to complete. Reaching this limit does not cause the drive to immediately fail; the TBW simply denotes the maximum number of writes that can be guaranteed.

A solid-state device does not fail upon reaching the specified TBW, but at some point after surpassing the TBW value (and based on manufacturing variance margins), the drive reaches the end-of-life point, at which time the drive goes into read-only mode. Because of such behavior, careful planning must be done to use SSDs in the application environments to ensure that the TBW of the drive is not exceeded before the required life expectancy.

For example, the 3.2TB P5600 drive has an endurance of 17,500 TB of total bytes written (TBW). This means that for full operation over five years, write workload must be limited to no more than 9,589 GB of writes per day, which is equivalent to 3.0 full drive writes per day (DWPD). For the device to last three years, the drive write workload must be limited to no more than 15,982 GB of writes per day, which is equivalent to 5.0 full drive writes per day.

Technical specifications

The following table present technical specifications for the Intel P5600 drives.

Table 2. Technical specifications

Feature	1.6 TB drive	3.2 TB drive	6.4 TB drive
Interface	PCIe 4.0 x4	PCIe 4.0 x4	PCIe 4.0 x4
Capacity	1.6 TB	3.2 TB	6.4 TB
SED encryption	None	None	None
Endurance (drive writes per day over 5 years)	3 DWPD	3 DWPD	3 DWPD
Endurance (total bytes written)	8.0 PB	17.5 PB	35.0 PB
Data reliability	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read	< 1 in 10 ¹⁷ bits read
MTBF, hours	2,000,000	2,000,000	2,000,000
IOPS read (4 KB blocks)	400,000	780,000	1,000,000
IOPS write (4 KB blocks)	118,000	230,000	260,000
Sequential read rate (PCIe 4.0)	3.5 GBps	7.0 GBps	7.0 GBps
Sequential write rate (PCIe 4.0)	1.7 GBps	3.5 GBps	4.3 GBps
Read access latency sequential*	10 µs	9 µs	9 µs
Write access latency sequential*	13 µs	12 µs	12 µs
Read access latency random*	78 µs	78 µs	78 µs
Write access latency random*	16 µs	14 µs	14 µs
Shock, operating	1,000 G (Max) at 0.5 ms	1,000 G (Max) at 0.5 ms	1,000 G (Max) at 0.5 ms
Vibration, max, operating	2.17 G _{RMS} (5-700 Hz)	2.17 G _{RMS} (5-700 Hz)	2.17 G _{RMS} (5-700 Hz)
Average power (Active Read / Active Write)	8.5 / 15 W	12.5 / 18 W	12.5 / 20 W

* Latency measured using 4 KB transfer size with queue depth = 1 on a random workload.

Server support

The following tables list the ThinkSystem servers that are compatible.

Table 3. Server support (Part 1 of 5)

Part Number	Description	AMD V3				2S Intel V3/V4						Multi Node V3	1S V3				
		SR635 V3 (7D9H / 7D9G)	SR655 V3 (7D9F / 7D9E)	SR645 V3 (7D9D / 7D9C)	SR665 V3 (7D9B / 7D9A)	ST650 V3 (7D7B / 7D7A)	SR630 V3 (7D72 / 7D73)	SR650 V3 (7D75 / 7D76)	SR630 V4 (7DG8 / 7DG9)	SR650 V4 (7DGC / 7DGD)	SR650a V4 (7DGC / 7DGD)	SD535 V3 (7DD8 / 7DD1)	SD530 V3 (7DDA / 7DD3)	SD550 V3 (7DD9 / 7DD2)	ST45 V3 (7DH4 / 7DH5)	ST50 V3 (7DF4 / 7DF3)	ST250 V3 (7DCF / 7DCE)
2.5-inch hot-swap drives																	
4XB7A17152	ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17153	ThinkSystem 2.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17154	ThinkSystem 2.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
3.5-inch hot-swap drives																	
4XB7A17155	ThinkSystem 3.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17156	ThinkSystem 3.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17157	ThinkSystem 3.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Trayless drives																	
4XB7A71356	ThinkSystem 2.5" 15mm U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A71357	ThinkSystem 2.5" 15mm U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 4. Server support (Part 2 of 5)

Part Number	Description	4S 8S Intel V3/V4					GPU Rich					Edge						
		SR850 V3 (7D97 / 7D96)	SR860 V3 (7D94 / 7D93)	SR950 V3 (7DC5 / 7DC4)	SR850 V4 (7DJT / 7DJS)	SR860 V4 (7DJQ / 7DJN)	SR670 V2 (7Z22 / 7Z23)	SR675 V3 (7D9Q / 7D9R)	SR680a V3 (7DHE)	SR680a V3 B200 (7DM9)	SR685a V3 (7DHC)	SR780a V3 (7DJ5)	SR680a V4 (7DMK)	SE100 (7DGR)	SE350 (7Z46 / 7D1X)	SE350 V2 (7DA9)	SE360 V2 (7DAM)	SE450 (7D8T)
2.5-inch hot-swap drives																		
4XB7A17152	ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A17153	ThinkSystem 2.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	Y	N	N	N	N	N	N	N	N	N	N	N
4XB7A17154	ThinkSystem 2.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	Y	N	N	N	N	N	N	N	N	N	N	N
3.5-inch hot-swap drives																		
4XB7A17155	ThinkSystem 3.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17156	ThinkSystem 3.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17157	ThinkSystem 3.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Trayless drives																		
4XB7A71356	ThinkSystem 2.5" 15mm U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A71357	ThinkSystem 2.5" 15mm U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 5. Server support (Part 3 of 5)

Part Number	Description	Super Computing					1S Intel V2	2S Intel V2	AMD V1									
		SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)	SR665 (7D2W / 7D2V)
2.5-inch hot-swap drives																		

Part Number	Description	Super Computing						1S Intel V2			2S Intel V2			AMD V1			
		SC750 V4 (7DDJ)	SC777 V4 (7DKA)	SD665 V3 (7D9P)	SD665-N V3 (7DAZ)	SD650 V3 (7D7M)	SD650-I V3 (7D7L)	SD650-N V3 (7D7N)	ST50 V2 (7D8K / 7D8J)	ST250 V2 (7D8G / 7D8F)	SR250 V2 (7D7R / 7D7Q)	ST650 V2 (7Z75 / 7Z74)	SR630 V2 (7Z70 / 7Z71)	SR650 V2 (7Z72 / 7Z73)	SR635 (7Y98 / 7Y99)	SR655 (7Y00 / 7Z01)	SR645 (7D2Y / 7D2X)
4XB7A17152	ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y
4XB7A17153	ThinkSystem 2.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y	Y
4XB7A17154	ThinkSystem 2.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	Y	Y	Y	Y	Y	Y
3.5-inch hot-swap drives																	
4XB7A17155	ThinkSystem 3.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	Y	Y
4XB7A17156	ThinkSystem 3.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	Y	Y	Y	N	N	Y	Y
4XB7A17157	ThinkSystem 3.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	Y	Y	N	N	Y	Y
Trayless drives																	
4XB7A71356	ThinkSystem 2.5" 15mm U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A71357	ThinkSystem 2.5" 15mm U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Table 6. Server support (Part 4 of 5)

Part Number	Description	Dense V2				4S V2	8S	4S V1		1S Intel V1					
		SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN650 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)	SR250 (7Y52 / 7Y51)
2.5-inch hot-swap drives															
4XB7A17152	ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	Y	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	N
4XB7A17153	ThinkSystem 2.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	Y	N	N	Y	Y	Y	Y	Y	Y	Y	N	N	N	N
4XB7A17154	ThinkSystem 2.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	Y	Y	Y	Y	Y	Y	N	N	N	N

Part Number	Description	Dense V2				4S V2	8S	4S V1			1S Intel V1			
		SD630 V2 (7D1K)	SD650 V2 (7D1M)	SD650-N V2 (7D1N)	SN550 V2 (7Z69)	SR850 V2 (7D31 / 7D32)	SR860 V2 (7Z59 / 7Z60)	SR950 (7X11 / 7X12)	SR850 (7X18 / 7X19)	SR850P (7D2F / 2D2G)	SR860 (7X69 / 7X70)	ST50 (7Y48 / 7Y50)	ST250 (7Y45 / 7Y46)	SR150 (7Y54)
3.5-inch hot-swap drives														
4XB7A17155	ThinkSystem 3.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17156	ThinkSystem 3.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A17157	ThinkSystem 3.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	N	N	N	N	N	N	N	N
Trayless drives														
4XB7A71356	ThinkSystem 2.5" 15mm U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	Y	Y	N	N	N	N	N	N	N	N	N	N
4XB7A71357	ThinkSystem 2.5" 15mm U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	Y	Y	N	N	N	N	N	N	N	N	N	N

Table 7. Server support (Part 5 of 5)

Part Number	Description	2S Intel V1							Dense V1				
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
2.5-inch hot-swap drives													
4XB7A17152	ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	Y	Y	Y	Y	N	Y	N	Y	Y
4XB7A17153	ThinkSystem 2.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	Y	Y	Y	Y	N	Y	N	Y	Y
4XB7A17154	ThinkSystem 2.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	Y	Y	Y	Y	N	Y	N	Y	Y
3.5-inch hot-swap drives													
4XB7A17155	ThinkSystem 3.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	Y	Y	N	N	N	N	N
4XB7A17156	ThinkSystem 3.5" U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	Y	Y	N	N	N	N	N
4XB7A17157	ThinkSystem 3.5" U.2 P5600 6.4TB Mixed Use NVMe PCIe 4.0 x4 HS SSD	N	N	N	N	N	Y	Y	N	N	N	N	N
Trayless drives													

Part Number	Description	2S Intel V1								Dense V1			
		ST550 (7X09 / 7X10)	SR530 (7X07 / 7X08)	SR550 (7X03 / 7X04)	SR570 (7Y02 / 7Y03)	SR590 (7X98 / 7X99)	SR630 (7X01 / 7X02)	SR650 (7X05 / 7X06)	SR670 (7Y36 / 7Y37)	SD530 (7X21)	SD650 (7X58)	SN550 (7X16)	SN850 (7X15)
4XB7A71356	ThinkSystem 2.5" 15mm U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N
4XB7A71357	ThinkSystem 2.5" 15mm U.2 P5600 3.2TB Mixed Use NVMe PCIe 4.0 x4 Trayless SSD	N	N	N	N	N	N	N	N	N	N	N	N

Storage controller support

NVMe PCIe SSDs require a NVMe drive backplane and some form of PCIe connection to processors. PCIe connections can take the form of either an adapter (PCIe Interposer or PCIe extender/switch adapter) or simply a cable that connects to an onboard NVMe connector.

PCIe 3.0 support: The Intel P5600 drives offer a PCIe 4.0 host interface, however they are backward compatible with a PCIe 3.0 host interface. Note however that servers with a PCIe 3.0 host interface will not see the same performance levels (especially sequential read and write rates). ThinkSystem NVMe switch adapters also provide a PCIe 3.0 host interface to attached drives.

Consult the relevant server product guide for details about required components for NVMe drive support.

Operating system support

The drives support the following operating systems:

Tip: These tables are automatically generated based on data from [Lenovo ServerProven](#).

Table 8. Operating system support for ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD, 4XB7A17152 (Part 1 of 2)

Operating systems	SR950 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2	SR670 V2	SR850 (Xeon Gen 1)	SR850 V2	SR850P (Xeon Gen 2)	SR860 (Xeon Gen 1)	SR860 V2	SR630 V2	SR950 (Xeon Gen 2)	ST650 V2	ST650 V2	SN550 (Xeon Gen 1)	SN850 (Xeon Gen 1)	SN550 V2	SD630 V2	SR850 (Xeon Gen 2)	SR590 (Xeon Gen 2)	SD530 (Xeon Gen 2)
Microsoft Windows 10	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Microsoft Windows 11	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Microsoft Windows Server 2012 R2	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
Microsoft Windows Server 2016	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2019	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server version 1709	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
Microsoft Windows Server version 1803	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	N	N	N	N	N	N
Red Hat Enterprise Linux 6.9	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 6.10	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 7.3	Y	Y	N	N	Y	N	N	N	N	N	N	N	N	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 7.4	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 7.5	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
Red Hat Enterprise Linux 7.6	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
Red Hat Enterprise Linux 7.7	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
Red Hat Enterprise Linux 7.8	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
Red Hat Enterprise Linux 7.9	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.0	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
Red Hat Enterprise Linux 8.1	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
Red Hat Enterprise Linux 8.2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

Operating systems	SR950 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2	SR670 V2	SR650 (Xeon Gen 1)	SR850 V2	SR850P (Xeon Gen 2)	SR860 (Xeon Gen 1)	SR860 V2	SR630 V2	SR950 (Xeon Gen 2)	ST650 V2	ST650 V2	SN550 (Xeon Gen 1)	SN850 (Xeon Gen 1)	SN550 V2	SD630 V2	SR850 (Xeon Gen 2)	SR590 (Xeon Gen 2)	SD530 (Xeon Gen 2)
Red Hat Enterprise Linux 8.9	N	N	Y	Y	N	Y	Y	N	Y	Y	Y	Y	Y	N	N	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.10	N	N	Y	Y	N	Y	N	N	Y	Y	Y	Y	Y	N	N	Y	Y	N	N	N
Red Hat Enterprise Linux 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	N	N	Y	Y	N	Y	Y	N	Y	Y	Y	Y	Y	N	N	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.4	N	N	Y	Y	N	Y	N	N	Y	Y	Y	Y	Y	N	N	Y	Y	N	N	N
SUSE Linux Enterprise Server 11 SP4	Y	Y	N	N	Y	N	N	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
SUSE Linux Enterprise Server 12 SP2	Y	Y	N	N	Y	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 12 SP2 with Xen	Y	Y	N	N	Y	N	N	N	N	N	N	N	N	N	Y	N	N	N	N	N
SUSE Linux Enterprise Server 12 SP3	Y	Y	N	N	Y	N	Y	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
SUSE Linux Enterprise Server 12 SP3 with Xen	Y	Y	N	N	Y	N	Y	Y	N	N	N	N	N	Y	Y	N	N	N	N	N
SUSE Linux Enterprise Server 12 SP4	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
SUSE Linux Enterprise Server 12 SP4 with Xen	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
SUSE Linux Enterprise Server 15 SP1	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
SUSE Linux Enterprise Server 15 SP1 with Xen	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
SUSE Linux Enterprise Server 15 SP2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP2 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

Operating systems	SR950 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2	SR670 V2	SR850 (Xeon Gen 1)	SR850 V2	SR850P (Xeon Gen 2)	SR860 (Xeon Gen 1)	SR860 V2	SR630 V2	SR950 (Xeon Gen 2)	ST650 V2	ST650 V2	SN550 (Xeon Gen 1)	SN850 (Xeon Gen 1)	SN550 V2	SD630 V2	SR850 (Xeon Gen 2)	SR590 (Xeon Gen 2)	SD530 (Xeon Gen 2)
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 with Xen	Y	Y	N	N	Y	N	Y	Y	N	N	Y	N	N	Y	Y	N	N	Y	Y	Y
Ubuntu 18.04.5 LTS or later with HWE kernel	N	N	Y	Y	N	N	N	N	N	Y	N	Y	Y	N	N	Y	Y	N	N	N
Ubuntu 20.04 LTS or later with HWE kernel	N	N	Y	N	N	N	N	N	N	Y	N	N	N	N	N	N	N	N	N	N
Ubuntu 22.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 24.04 LTS or later with HWE kernel	N	N	Y	Y	N	Y	N	N	Y	Y	N	Y	Y	N	N	Y	Y	N	N	N
VMware vSphere Hypervisor (ESXi) 6.0 U3	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	N	N	N	N	N	Y ¹	Y ¹	N	N	N	N	N
VMware vSphere Hypervisor (ESXi) 6.5	Y ¹	Y ¹	N	N	Y ¹	N	N	N	N	N	N	N	N	Y ¹	Y ¹	N	N	N	N	N
VMware vSphere Hypervisor (ESXi) 6.5 U1	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	N	N	N	N	N	Y ¹	Y ¹	N	N	N	N	N
VMware vSphere Hypervisor (ESXi) 6.5 U2	Y ¹	Y ¹	N	N	Y ¹	N	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	Y ¹	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.5 U3	Y ¹	Y ¹	N	N	Y ¹	N	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	Y ¹	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.7	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	N	N	N	N	N	Y ¹	Y ¹	N	N	N	N	N
VMware vSphere Hypervisor (ESXi) 6.7 U1	Y ¹	Y ¹	N	N	Y ¹	N	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	Y ¹	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.7 U2	Y ¹	Y ¹	N	N	Y ¹	N	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	Y ¹	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.7 U3	Y ¹	Y ¹	Y	Y	Y ¹	N	Y ¹	Y ¹	N	Y	Y ¹	Y	Y	Y ¹	Y ¹	Y	Y	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 7.0	Y ¹	Y ¹	N	N	Y ¹	N	Y ¹	Y ¹	N	N	Y ¹	N	N	Y ¹	Y ¹	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 7.0 U1	Y	Y	N	N	Y	Y	Y	Y	Y	N	Y	N	N	Y	Y	N	N	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

Operating systems	SR950 (Xeon Gen 1)	SR650 (Xeon Gen 1)	SR650 V2	SR670 V2	SR850 (Xeon Gen 1)	SR850 V2	SR850P (Xeon Gen 2)	SR860 (Xeon Gen 1)	SR860 V2	SR630 V2	SR950 (Xeon Gen 2)	ST650 V2	ST650 V2	SN550 (Xeon Gen 1)	SN850 (Xeon Gen 1)	SN550 V2	SD630 V2	SR850 (Xeon Gen 2)	SR590 (Xeon Gen 2)	SD530 (Xeon Gen 2)
	VMware vSphere Hypervisor (ESXi) 8.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	N	Y	Y	Y

¹ VMware ESXi boot support: It is currently not supported to install the bootable Lenovo VMware Customized Image on P5600 drives. Support is planned for late 4Q2020.

Table 9. Operating system support for ThinkSystem 2.5" U.2 P5600 1.6TB Mixed Use NVMe PCIe 4.0 x4 HS SSD, 4XB7A17152 (Part 2 of 2)

Operating systems	SN550 (Xeon Gen 2)	SN850 (Xeon Gen 2)	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR570 (Xeon Gen 2)	SR860 (Xeon Gen 2)	SD530 (Xeon Gen 1)	SR635	SR655	SR645	SR665	SR570 (Xeon Gen 1)	SR590 (Xeon Gen 1)	SR630 (Xeon Gen 1)
	Microsoft Windows 10	N	N	N	N	N	N	N	N	Y ³	N	N	N	N
Microsoft Windows 11	N	N	N	N	N	N	N	N	Y ³	N	N	N	N	N
Microsoft Windows Server 2012 R2	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y
Microsoft Windows Server 2016	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2019	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server 2022	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Microsoft Windows Server version 1709	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y
Microsoft Windows Server version 1803	N	N	N	N	N	N	Y	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 6.9	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y
Red Hat Enterprise Linux 6.10	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y
Red Hat Enterprise Linux 7.3	N	N	N	N	N	N	Y	N	N	N	N	N	N	Y
Red Hat Enterprise Linux 7.4	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y
Red Hat Enterprise Linux 7.5	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y
Red Hat Enterprise Linux 7.6	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y
Red Hat Enterprise Linux 7.7	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y
Red Hat Enterprise Linux 7.8	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y
Red Hat Enterprise Linux 7.9	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y
Red Hat Enterprise Linux 8.0	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	N	N	Y	Y	Y
Red Hat Enterprise Linux 8.1	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y

	SN550 (Xeon Gen 2)	SN850 (Xeon Gen 2)	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR570 (Xeon Gen 2)	SR860 (Xeon Gen 2)	SD530 (Xeon Gen 1)	SR635	SR655	SR645	SR665	SR570 (Xeon Gen 1)	SR590 (Xeon Gen 1)	SR630 (Xeon Gen 1)	
Operating systems															
Red Hat Enterprise Linux 8.2	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y	Y
Red Hat Enterprise Linux 8.3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.6	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.7	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.8	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 8.9	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 8.10	N	N	N	Y	N	N	N	Y	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 9.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Red Hat Enterprise Linux 9.3	Y	Y	Y	Y	Y	Y	N	Y	Y	Y	Y	N	N	N	N
Red Hat Enterprise Linux 9.4	N	N	N	N	N	N	N	Y	Y	Y	Y	N	N	N	N
SUSE Linux Enterprise Server 11 SP4	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP2	N	N	N	N	N	N	Y	N	N	N	N	N	N	Y	Y
SUSE Linux Enterprise Server 12 SP2 with Xen	N	N	N	N	N	N	Y	N	N	N	N	N	N	Y	Y
SUSE Linux Enterprise Server 12 SP3	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP3 with Xen	N	N	N	N	N	N	Y	N	N	N	N	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP4	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	N	N	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP4 with Xen	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	N	N	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 12 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP1	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP1 with Xen	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y ²	Y ²	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP2 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP3 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP4 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 SP5 with Xen	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
SUSE Linux Enterprise Server 15 with Xen	Y	Y	Y	Y	Y	Y	Y	N	N	N	N	Y	Y	Y	Y
Ubuntu 18.04.5 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N
Ubuntu 20.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	N	N	N	N	N	N	N	N

Operating systems	SN550 (Xeon Gen 2)	SN850 (Xeon Gen 2)	SR630 (Xeon Gen 2)	SR650 (Xeon Gen 2)	SR570 (Xeon Gen 2)	SR860 (Xeon Gen 2)	SD530 (Xeon Gen 1)	SR635	SR655	SR645	SR665	SR570 (Xeon Gen 1)	SR590 (Xeon Gen 1)	SR630 (Xeon Gen 1)
Ubuntu 22.04 LTS or later with HWE kernel	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
Ubuntu 24.04 LTS or later with HWE kernel	N	N	N	N	N	N	N	Y	Y	Y	Y	N	N	N
VMware vSphere Hypervisor (ESXi) 6.0 U3	N	N	N	N	N	N	Y ¹	N	N	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.5	N	N	N	N	N	N	Y ¹	N	N	N	N	N	N	Y ¹
VMware vSphere Hypervisor (ESXi) 6.5 U1	N	N	N	N	N	N	Y ¹	N	N	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.5 U2	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	N	N	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.5 U3	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ²	Y ²	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.7	N	N	N	N	N	N	Y ¹	N	N	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.7 U1	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	N	N	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.7 U2	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	N	N	N	N	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 6.7 U3	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y	Y	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 7.0	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ¹	Y ²	Y ²	Y ²	Y ²	Y ¹	Y ¹	Y ¹
VMware vSphere Hypervisor (ESXi) 7.0 U1	Y	Y	Y	Y	Y	Y	Y	Y ²	Y ²	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 7.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U1	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U2	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y
VMware vSphere Hypervisor (ESXi) 8.0 U3	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y	Y

¹ VMware ESXi boot support: It is currently not supported to install the bootable Lenovo VMware Customized Image on P5600 drives. Support is planned for late 4Q2020.

² The OS is not supported with EPYC 7003 processors.

³ ISG will not sell/preload this OS, but compatibility and cert only.

Warranty

The SSDs carry a 1-year, customer-replaceable unit (CRU) limited warranty. When installed in a supported Lenovo server, these drives assume the server's base warranty and any warranty upgrade.

Solid State Memory cells have an intrinsic, finite number of program/erase cycles that each cell can incur. As a result, each solid state device has a maximum amount of program/erase cycles to which it can be subjected. The warranty for Lenovo solid state drives (SSDs) is limited to drives that have not reached the maximum guaranteed number of program/erase cycles, as documented in the Official Published Specifications for the SSD product. A drive that reaches this limit may fail to operate according to its Specifications.

Physical specifications

The Intel P5500 drives have the following physical dimensions and weight:

- Height: 15 mm (0.6 in.)
- Width: 70 mm (2.8 in.)
- Depth: 100 mm (4.0 in.)
- Weight: 146 g (5.15 oz)

Operating environment

The Intel P5600 drives are supported in the following environment:

- Temperature (operational): 0 to 70 °C (32 to 158 °F) at 0 to 3,048 m (0 to 10,000 ft)
- Relative humidity: 5 to 90% (non-condensing)
- Maximum altitude (operational): 3,048 m (10,000 ft)
- Shock: 1,000 G (Max) at 0.5 ms
- Vibration: 2.17 G_{RMS} (5-700 Hz)

Agency approvals

The Intel P5600 drives conform to the following regulations:

- FCC Title 47, Part 15B, Class B
- CA/CSA-CEI/IEC CISPR 22:02
- EN 55024: 1998
- EN 55022: 2006
- EN-60950-1 2nd Edition
- UL/CSA EN-60950-1 2nd Edition
- Low Voltage Directive 2006/95/EC
- C-Tick: AS/NZS3584
- BSMI: CNS 13438
- KCC Article 11.1
- RoHS DIRECTIVE 2011/65/EU
- WEEE Directive 2002/96/EC

Related publications and links

For more information, see the following documents:

- Storage Options for ThinkSystem Servers
<https://lenovopress.com/lp0761-storage-options-for-thinksystem-servers>
- ServerProven
<http://www.lenovo.com/us/en/serverproven>

Related product families

Product families related to this document are the following:

- [Drives](#)

Notices

Lenovo may not offer the products, services, or features discussed in this document in all countries. Consult your local Lenovo representative for information on the products and services currently available in your area. Any reference to a Lenovo product, program, or service is not intended to state or imply that only that Lenovo product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any Lenovo intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any other product, program, or service. Lenovo may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to:

Lenovo (United States), Inc.
8001 Development Drive
Morrisville, NC 27560
U.S.A.
Attention: Lenovo Director of Licensing

LENOVO PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. Lenovo may make improvements and/or changes in the product(s) and/or the program(s) described in this publication at any time without notice.

The products described in this document are not intended for use in implantation or other life support applications where malfunction may result in injury or death to persons. The information contained in this document does not affect or change Lenovo product specifications or warranties. Nothing in this document shall operate as an express or implied license or indemnity under the intellectual property rights of Lenovo or third parties. All information contained in this document was obtained in specific environments and is presented as an illustration. The result obtained in other operating environments may vary. Lenovo may use or distribute any of the information you supply in any way it believes appropriate without incurring any obligation to you.

Any references in this publication to non-Lenovo Web sites are provided for convenience only and do not in any manner serve as an endorsement of those Web sites. The materials at those Web sites are not part of the materials for this Lenovo product, and use of those Web sites is at your own risk. Any performance data contained herein was determined in a controlled environment. Therefore, the result obtained in other operating environments may vary significantly. Some measurements may have been made on development-level systems and there is no guarantee that these measurements will be the same on generally available systems. Furthermore, some measurements may have been estimated through extrapolation. Actual results may vary. Users of this document should verify the applicable data for their specific environment.

© Copyright Lenovo 2025. All rights reserved.

This document, LP1354, was created or updated on January 20, 2023.

Send us your comments in one of the following ways:

- Use the online Contact us review form found at:
<https://lenovopress.lenovo.com/LP1354>
- Send your comments in an e-mail to:
comments@lenovopress.com

This document is available online at <https://lenovopress.lenovo.com/LP1354>.

Trademarks

Lenovo and the Lenovo logo are trademarks or registered trademarks of Lenovo in the United States, other countries, or both. A current list of Lenovo trademarks is available on the Web at <https://www.lenovo.com/us/en/legal/copytrade/>.

The following terms are trademarks of Lenovo in the United States, other countries, or both:

Lenovo®

ServerProven®

ThinkSystem®

The following terms are trademarks of other companies:

AMD is a trademark of Advanced Micro Devices, Inc.

Intel®, the Intel logo and Xeon® are trademarks of Intel Corporation or its subsidiaries.

Linux® is the trademark of Linus Torvalds in the U.S. and other countries.

Microsoft®, Windows Server®, and Windows® are trademarks of Microsoft Corporation in the United States, other countries, or both.

Other company, product, or service names may be trademarks or service marks of others.