


## VisionTek DLX4 2280 M.2 PCIe 4.0 x4 SSD (NVMe)

SKU: 901564

MSRP: \$84.99



Powered by the Innogrit IG5220 controller, VisionTek DLX4 M.2 NVMe SSDs offers speed and reliability for professionals, gamers and everyday users. With read speeds up to 5200MB/s and write speeds up to 4775MB/s take your storage to the next level.


- Max Sequential Reads up to 5200MB/s
- Max Sequential Writes up to 4775MB/s
- Max 4K Random Reads up to 370K IOPS
- Max 4K Random Writes up to 288K IOPS

## VisionTek DLX4 M.2 PCIe 4.0 x4 SSD (NVMe)

The VisionTek DLX4 M.2 NVMe SSD is designed to bring ultra-fast, reliable storage to PC users. With the shift from the hard disk drive to the solid state drive the VisionTek DLX4 M.2's provide a drop-in replacement option for the hard disk drive (HDD) for M.2 NVMe compatible systems. It delivers superior reliability, durability, performance and power efficiency - keeping your system working reliably in the toughest of conditions.


Conforming to the industry standard NVMe connector specification, these SSDs integrate easily into compatible infrastructures. The VisionTek DLX4 Pro M.2's provide high bandwidth and IOPS while efficiently managing write amplification. Employing M.2 NVMe SSDs in a compatible system enables faster boot times, quicker application load times, lower power consumption, and enhanced reliability.

### Speed / Performance



Start your system in seconds, load files almost instantly, and accelerate the most demanding applications with VisionTek solid state drives. With the advancements in SSD technology, you can open a program and have it load immediately. Unlike a mechanical hard drive, an SSD has no moving parts ensuring faster performance, longer device life and more secure data.

### Easy to Install



A solid state hard drive is easy to install, in just a few minutes time you can upgrade your internal system storage. No need to pay someone else, the installation of an SSD is quick and easy! Consult your system manufacturers documentation for system specific installation instructions.

## Features

- SLC caching accelerates burst performance
- 3D NAND
- PCIe Gen4 x4
- Global wear leveling
- StaticDataRefresh technology ensures data integrity
- Data shaping increases endurance
- Intelligent garbage collection routines for advanced free space management
- NVMe Deallocate function support (NVMe equivalent of TRIM command)
- Host memory Buffer (HMB) support (OS dependent)
- S.M.A.R.T. (Self-Monitoring, Analysis, and Reporting Technology) support
- Performance optimized LDPC engine
- NVMe Protocol 1.4 compliant
- RoHS Compliant

## Technical Specifications

### Connection Type

M.2 (M Key)

### Form Factor

M.2 2280

### Controller

Innogrit IG5220

### Flash Type

3D NAND

### Security

NVMe Security Erase support  
OPAL 2.0 Support  
256-bit AES Compliant Data Encryption

### Reliability

MTBF: 1.5 million device hours\*  
Low Density Parity Check (LDPC) ECC  
Static and dynamic wear leveling  
Uncorrectable Bit Error Rate: ?1 sector per  $10^{15}$  bits read

### Electrical / Mechanical

+3.3VDC ( $\pm 5\%$ ) power supply  
Power Consumption: up to 4.75W (Active), 0.3W (Idle)  
M.2 2280: 22.0 mm x 80.0 mm  
Weight: 7g

### Environmental

Operating temperature: 0-70°C  
Non-Operating temperature: -40-85°C  
Operating humidity: 5-95% relative  
Shock: 1500G/0.5ms  
Vibration: 2-500Hz, 3.1G

## Performance

Part #	Capacity	Max Sequential Reads	Max Sequential Writes	Max 4K Random Reads	Max 4K Random Writes	Endurance
901564	512GB	4725 MB/s	2525 MB/s	195K IOPS	289K IOPS	TBW: Up to 250TB
901565	1TB	5200 MB/s	4370 MB/s	195K IOPS	289K IOPS	TBW: Up to 500TB
901566	2TB	4985 MB/s	4775 MB/s	336K IOPS	288K IOPS	TBW: Up to 1000TB

## Warranty

### Warranty:

5 Year Limited Warranty\*

- A period of 5 years from purchase date with registration -AND-
- (901564 / 512GB) - Up to 250TB Maximum Total Bytes Written (TBW) to flash by capacity -OR-
- (901565 / 1TB) - Up to 500TB Maximum Total Bytes Written (TBW) to flash by capacity -OR-
- (901566 / 2TB) - Up to 1000TB Maximum Total Bytes Written (TBW) to flash by capacity -OR-
- Up to 250 insertion/removal cycles to the host

Product must be registered within 30 days of purchase to be covered by the 5 Year Limited Warranty\*. Products not registered within 30 days of purchase will default to our 1-Year Warranty period.

You may register your product here: [www.visiontek.com/support/warranty-registration](http://www.visiontek.com/support/warranty-registration)

For additional warranty information, please see our Warranty Page: [www.visiontek.com/support/warranty-information](http://www.visiontek.com/support/warranty-information)

## Support

## Spec Sheet

Please Wait...

## FAQ

For California Residents Only:

**WARNING: Cancer and Reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)**

\* Please, Note that Proposition 65 may be best defined as a “Right To Know” law in California and Prop 65 warning labels are not an indication that a product is violating safety standards or regulations. The Prop 65 warning label does not mean our products inevitably cause cancer or reproductive harm. We do not consider our products harmful when used as intended. However, it is a necessary precaution to provide the warning because of this California law.