



QuickNet™ Trunk Cable Assembly

FWUYL7575KNM049

OM5, 24 Fiber Trunk, Low Smoke Zero Halogen, PanMPO Female to PanMPO Female, HD Flex Transition, Method A, Ultra Insertion Loss - 49 Meters

Specifications

Fiber Type	OM5
Number of Fibers	24
Sub Brand	QuickNet™
Flammability Rating	LSZH
Fiber Diameter (µm)	50
Overall Length (ft.)	160.76
Overall Length (m)	49
Fiber Polarity	Method A
Cable Color	Lime
Pulling Eye	No
Product Type	Trunk Cable Assembly
Standards Met	Meets or exceeds ISO/IEC 11801, TIA/EIA-568-C.3, TIA-604-5 (FOCIS-5), TIA/EIA-568-C.1, RoHS compliant, TIA-492-AAAD, IED 60793-2-10 type A1a.3
Application	Data centers requiring quick infrastructure deployment with extended reach. Small diameter trunk cable assemblies use 30 to 40% less space which is ideal for high density cable applications

Packaging Detail

UPC	61305635199
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	0.9400
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000