

B




A

B-SIZE CUSTOMER

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PLENUM CABLE		
FIBERS	CABLE TYPE	DIA. (INCHES)
12	SMALL DIA. INDOOR	.19
24	SMALL DIA. INDOOR	.21
48	SMALL DIA. INDOOR	.22
72	SMALL DIA. INDOOR	.26
96	SMALL DIA. INDOOR	.32
144	SMALL DIA. INDOOR	.37


- NOTES:
1. VISIT OUR ON-LINE CATALOG AT WWW.PANDUIT.COM FOR A LIST OF CURRENT PARTS APPLICABLE FOR USE WITH THIS PRODUCT.
 2. ALL MATERIALS AND COMPONENTS USED MEET THE MATERIAL RESTRICTIONS OF RoHS (EUROPEAN DIRECTIVE 2011/65/EU ON THE RESTRICTION OF HAZARDOUS SUBSTANCES) AS PROPOSED BY THE RoHS TECHNICAL ADAPTATION COMMITTEE.
 3. SINGLEMODE MPO AND SINGLEMODE PANMPO ARE ANGLED POLISH (APC)



CONNECTORS	
12F FEMALE MPO	
12F MALE MPO	
12F FEMALE PANMPO	
12F MALE PANMPO	
24F FEMALE MPO	
24F MALE MPO	

TRANSITIONS	
HD FLEX	
STANDARD TUBE	VARIOUS STYLES

SEE "SERIAL" COLUMN IN TABLE LOCATED ON SHEET 2.



TYPICAL PULLING EYE

NOMINAL PULLING EYE DIAMETERS FOR PANMPO/MPO TRUNKS	
FIBERS	INCHES
12	1.1"
24	1.1"
48	2.1"
72	2.1"
96	2.1"
144	2.1"
PIGTAILS	1.1"

00D	5/30/23	JSP	FJDU	EJH	D. REMOVED OM5 FROM DRAWING, SEE 01608AAH-DC.	0160AAC-DC
00C	04-10-23	SAT	FJDU	EJH	C. ADDED ADDED, 008 STANDARD PIGTAIL WITHOUT PULLING EYE. B. ADDED METHOD FIBER COLOR KEY TABLES	0160AAC-DC
00B	11-18-20	SAT	FJDU	EJH	A. CORRECTED OPTIMIZED TYPO.	0160AAC-DC
00A	10/29/19	JSP	FJDU	EJH	INITIAL RELEASE	0160AAC-DC
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

FOR PIGTAILS ONLY

FIBER 1

FIBER 1

METHOD A FIBER COLOR KEY	METHOD B FIBER COLOR KEY
FIBER 1 - BLUE	FIBER 1 - AQUA
FIBER 2 - ORANGE	FIBER 2 - ROSE
FIBER 3 - GREEN	FIBER 3 - VIOLET
FIBER 4 - BROWN	FIBER 4 - YELLOW
FIBER 5 - SLATE	FIBER 5 - BLACK
FIBER 6 - WHITE	FIBER 6 - RED
FIBER 7 - RED	FIBER 7 - WHITE
FIBER 8 - BLACK	FIBER 8 - SLATE
FIBER 9 - YELLOW	FIBER 9 - BROWN
FIBER 10 - VIOLET	FIBER 10 - GREEN
FIBER 11 - ROSE	FIBER 11 - ORANGE
FIBER 12 - AQUA	FIBER 12 - BLUE

SINGLEMODE METHOD A AND METHOD B PANMPO ARE NOT POLARITY REVERSIBLE.

PART NUMBER		SEE CONFIGURATOR ON SHEET 2	
TITLE		CONFIGURE TO ORDER 12F TO 144F MPO/PanMPO TRUNK PLENUM CABLES	
ITEM REVISION NAME		CUSTOMER DRAWING	
01608AAC/00			
DATASET FILE NAME			
01608AAC_DC/00D			
		THIRD ANGLE PROJECTION	
MATERIAL		DRAWING NUMBER	
MULTIPLE		01608AAC-DC	
DRAWN BY	DATE	CHK	SCALE
JSP	10/28/19	FJDU	NONE
SHEET 1 OF 2			SIZE
			B

B



A

B

A


B-SIZE CUSTOMER

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

CHARACTER	1	2	3	4	5	6	7	8	9-11	12	13-15
ATTRIBUTE	FIBER	PRODUCT/CABLE TYPE	FIBER TYPE	FIBER COUNT	FLAME RATING	CONNECTOR TYPE (END 'A')	CONNECTOR TYPE (END 'B')	POLARITY/PERFORMANCE	SERIAL	UNITS	LENGTH (TIP TOTIP)
OPTIONS	F	Y= SMALL DIA INDOOR TRUNK	9= SM	T= 12F	P= PLENUM (OFNP)	5= 12F MPO, FEMALE	5= 12F MPO, FEMALE	A= POLARITY A- STANDARD IL	XXX= SEE TABLE BELOW	F= FEET	015 - 999 FEET 5 - 400 METERS
			S= OM4+	U= 24F		6= 12F MPO, MALE	6= 12F MPO, MALE	B= POLARITY B- STANDARD IL		M= METERS	
			X= OM3	W= 48F		7= 12F PANMPO, FEMALE	7= 12F PANMPO, FEMALE	K= POLARITY A- ULTRA LOW IL			
			Z= OM4	X= 72F		8= 12F PANMPO, MALE	8= 12F PANMPO, MALE	L= POLARITY B- ULTRA LOW IL			
				Y= 96F		E= 24F MPO, FEMALE	E= 24F MPO, FEMALE	X= POLARITY A- OPTIMIZED IL			
				A= 144F		F= 24F MPO, MALE	F= 24F MPO, MALE	Y= POLARITY B- OPTIMIZED IL			
							U= PIGTAIL				

"SERIAL" COLUMN FROM ABOVE						
SERIAL #	TRANSITION TYPE	BREAKOUT A LENGTH	BREAKOUT B LENGTH	PULLING EYE	DESCRIPTION	
001	HD FLEX	1 METER	1 METER	END A ONLY	HD FLEX WITH PULLING EYE	
002				NONE	HD FLEX WITHOUT PULLING EYE	
003			NONE	END B ONLY	HD FLEX PIGTAIL WITH PULLING EYE	
005	STANDARD		1 METER	END A ONLY	STANDARD WITH PULLING EYE	
006				NONE	STANDARD WITHOUT PULLING EYE	
007				NONE	END B ONLY	STANDARD PIGTAIL WITH PULLING EYE
008				NONE	NONE	STANDARD PIGTAIL WITHOUT PULLING EYE

					SEE REVISIONS ON SHEET 1	0160AAC-DC
REV	DATE	BY	CHK	APR	DESCRIPTION	ECN

PART NUMBER						
SEE CONFIGURATOR ABOVE						
TITLE						
CONFIGURE TO ORDER 12F TO 144F MPO/PanMPO TRUNK PLENUM CABLES						
CUSTOMER DRAWING						
ITEM REVISION NAME				01608AAC/00		
DATASET FILE NAME				01608AAC_DC/00D		
				THIRD ANGLE PROJECTION		
MATERIAL				MULTIPLE		DRAWING NUMBER
						01608AAC-DC
DRAWN BY	DATE	CHK	SCALE	SHEET 2 OF 2		SIZE
JSP	10/28/19	FJDU	NONE			B

B

A