

APC SurgeArrest Performance Rackmount, 7x AS-NZS and 1x C13 Outlet, IEC C14 Plug, 6.5ft/2m cord + APC Power Cord, IEC C13 to AS/ NZS 3112 (AU) Plug

NET8RMIB-AZ

Overview

Lead time Usually in Stock

Main

Main Input Voltage	240 V AC
Main Output Voltage	240 V AC
Input Connection Type	IEC 60320 C14
Number of rack unit	1U
Cable length	2 m
Number of cables	1

Physical

Colour	Black
Height	44 mm
Width	441 mm
Depth	95 mm
Net weight	1.8 kg
Mounting support	Rack Wall
Mounting preference	No preference
Mounting mode	Rack-mounted
USB compatible	No

Input

Network frequency	50 Hz +/- 3 Hz
Plug standard	C14
Maximum input current	10 A
Switching current capacity	10 A

Output

Number of power socket outlets

Outlet standard	Australian IEC 320 C13	
Outlet standard	Australian IEC 60320 C13	

Conformance

Product certifications	RCM AS/NZS
Marking	RCM
Standards	AS/NZ 3112 AS/NZS 60320.1

Environmental

Ambient air temperature for operation	040 °C
Operating altitude	03000 m
Ambient air temperature for storage	-1545 °C
Storage Relative Humidity	095 %
Storage altitude	015000 m

Surge Protection and Filtering

Common mode rejection	40 dB
Surge energy rate	2400 J

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.9 cm
Package 1 Width	51.3 cm
Package 1 Length	23.5 cm
Package 1 Weight	2.025 kg

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
RoHS exemption information	Yes	

Contractual warranty

Recommended replacement(s)