



## Slit Nylon CLT, Flame Retardant, .256" (6.5mm) x 2952' (900m), ORG

CLT25NFR-3

The CLT25NFR-3 Corrugated Loom Tubing protects cables from impact and abrasion. Features a lengthwise slit for easy installation onto a bundle of wires. Hold in place with cable ties and accessories. Suitable for Electric Vehicles. UL94-V2 flammability rating and a maximum temperature rating of 275°F (135°C). Flame Retardant Polyimide. Inside diameter 0.26" (6.5mm). Color Orange. 2952 ft. (900m) Std. Pkg. 1 per package.

### Specifications

|                                    |                                                                     |
|------------------------------------|---------------------------------------------------------------------|
| Product Type                       | Corrugated Loom Tubing                                              |
| Color                              | Orange                                                              |
| Environment                        | Outdoor                                                             |
| Flammability Rating                | UL94V-2                                                             |
| Inside Diameter (In.)              | 0.26                                                                |
| Inside Diameter (mm)               | 6.5                                                                 |
| Material                           | Nylon 6                                                             |
| Resistance Properties              | Abrasion-Resistant                                                  |
| Minimum Operating Temperature (°C) | -40                                                                 |
| Minimum Operating Temperature (°F) | -40                                                                 |
| Maximum Operating Temperature (°C) | 135                                                                 |
| Maximum Operating Temperature (°F) | 275                                                                 |
| Nominal Diameter (In.)             | 0.26                                                                |
| Nominal Diameter (mm)              | 6.5                                                                 |
| Outer Diameter (In.)               | 0.39                                                                |
| Outer Diameter (mm)                | 10                                                                  |
| Overall Length (ft.)               | 2952                                                                |
| Overall Length (m)                 | 900                                                                 |
| Standards Met                      | RoHS Compliant                                                      |
| Part Features                      | Provides protection for cables, crush impact and abrasion resistant |

**Packaging Detail**

|                       |             |
|-----------------------|-------------|
| UPC                   | 61305689011 |
| Std. Pkg. Qty.        | 1           |
| Std. Pkg. Volume (cf) | 5.0182      |
| Std. Ctn. Qty.        | 0           |
| Std. Ctn. Volume (cf) | 0.0000      |