

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5535V

rev20180131

### LINE DRAWING



### FEATURES

|                                     |                                                                                                                                                                                                                          |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Energy Metering                     | Voltage (V), Current (A), Active Power (kW), Real Power (kVA), Energy (kWh), Power Factor                                                                                                                                |
| Metering Accuracy                   | ISO/IEC 62053-21 1%                                                                                                                                                                                                      |
| Metering per Input Line             | Yes                                                                                                                                                                                                                      |
| Metering per Branch Circuit Breaker | Yes                                                                                                                                                                                                                      |
| Metering per Output Receptacle      | Yes                                                                                                                                                                                                                      |
| Remote Outlet Switching             | Yes                                                                                                                                                                                                                      |
| Environmental Sensor Ready          | Yes                                                                                                                                                                                                                      |
| Replaceable Controller              | Yes                                                                                                                                                                                                                      |
| Compatible Sensors                  | Temperature, Humidity, Air Flow, Differential Pressure, Water Leak, and Contact Closure                                                                                                                                  |
| Networking                          | Gigabit (10/100/1000 BaseT) Ethernet port; secondary, redundant (10/100 BaseT) Ethernet port. Optional WiFi (802.11a/b/g/n)                                                                                              |
| Remote Management                   | HTTP(s); SSH; Telnet; RS-232 (Serial); Power IQ; SNMP version v2/v3; SMTP; JSON-RPC                                                                                                                                      |
| Cascading                           | Yes, Max 16 PDUs can be daisy chained using a single Ethernet or USB connection                                                                                                                                          |
| Onboard Display                     | Color, matrix LCD display : Voltage, current, or active power (per line, per breaker, or per receptacle / outlet); Alarms; Configuration information (name, ratings, IP / Networking information); Auto-flip orientation |
| Embedded Processor                  | ARM Cortex A5 536MHZ (Atmel A5D35A), 16MB SPI Flash, 64MB DDR2 RAM                                                                                                                                                       |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5535V

rev20180131

### INPUT

|                       |                                  |
|-----------------------|----------------------------------|
| Input Plug            | CS8365C (3P4W)                   |
| Cord Length           | 3 meters (9.84 feet) standard    |
| Cord Entry            | Bottom-bottom feed               |
| Cable Type            | IP20                             |
| Number of Power Cords | 1                                |
| Maximum Input Current | 50A                              |
| Nominal Input Voltage | 208V 3 phase                     |
| Rated Input Voltage   | 208 - 240V 3 phase               |
| Input Frequency       | 50/60Hz                          |
| Power Capacity        | 12.6kVA at 208V, 14.5kVA at 240V |

### OUTPUT

|                                  |                                             |
|----------------------------------|---------------------------------------------|
| Nominal Output Voltage           | 208V                                        |
| Rated Output Voltage             | 208 - 240V                                  |
| Receptacles (Output Connections) | (18) IEC320 C13, 12A<br>(6) IEC320 C19, 16A |
| Securelock Support               | Yes                                         |
| Cord Retention                   | Yes                                         |
| Overload Protection              | (3) LEGBXA66-20                             |

### PHYSICAL

|                             |                                                  |
|-----------------------------|--------------------------------------------------|
| Color                       | Black powder coat (custom colors available)      |
| Unit Dimensions (WxDxH)     | 2.1" x 2.6" x 70.1" ; 52mm x 65mm x 1780mm       |
| Unit Weight                 | TBD                                              |
| Shipping Weight             | TBD                                              |
| Shipping Dimensions (WxDxH) | 11.02" x 4.53" x 80.91" ; 280mm x 115mm x 2055mm |
| Mounting                    | G2-RACK-FOR-ZU                                   |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5535V

rev20180131

### ENVIRONMENTAL

|                             |           |
|-----------------------------|-----------|
| Operating Temperature       | 60°C      |
| Operating Relative Humidity | 85%       |
| Operating Elevation         | 0-10000ft |

### CONFORMANCE


|                      |                                                                              |
|----------------------|------------------------------------------------------------------------------|
| Regulatory Approvals | UL Listed, Canada ICES-003, Part 15 Class A of the FCC rules, RoHS compliant |
| Warranty             | Standard 2 years manufacturer warranty                                       |

## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5535V

rev20180131

### CONTROL PANEL




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5535V

rev20180131

### ELECTRICAL (ONE LINE) DIAGRAM



Raritan Model Number: PX3-5535V

QF70455

## 6



## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5535V


rev20180131

### Mounting Diagram (G2-RACK-FOR-ZU)



250-70-0104-00






250-80-0011-00



**250-70-0007-00**



**250-70-0093-00**




## Technical Specifications / Engineering Submittals

Raritan Model Number: PX3-5535V

rev20180131

### TRIP CURVE



This file generated on: Wed, January 31, 2018 - 03:12:03