

BEST SELLER



MS PDU, 32AMP, 400 V, (24)C13, (12)C19, (IP44)

P36E09M

This Panduit™ G5 Monitored Switched PDU features (24) C13 and (12) C19 outlets. It is a 32 amp, 400 V, three phase PDU with an IEC 60309 3P+N+E 6h 32A (IP44) input plug and a 10 foot (3m) power cord.

Specifications

Note	CE Compliant Only
Includes	Mounting Hardware
Product Type	PDU
Mount Orientation	Vertical
Sub Brand	G5
Rack PDU Type	Monitored & Switched
Plug Type	IEC 60309 3P+N+E 6h 32A (IP44)
Number of Circuit Breakers	6
Input Voltage (V)	415
Input Amperage (A)	32
Phase	3 Phase
Frequency Compatibility (Hz)	50/60
Current Measurement Accuracy (%)	±1%
Voltage Measurement Accuracy (%)	±1%
Power Measurement Accuracy (%)	±1%
Input Cord Length (ft.)	3
Input Cord Length (m)	10
Output Receptacles	(24)C13, (12)C19
Output Voltage (V)	230
Output Capacity (kW)	22
Front Panel Display	Use display to set IP address, update firmware, quick configure, rotate display, balance loads across phases, view alarms, read current, voltage, power and energy on the device
Network Monitoring Port	Gigabit network port reduces labor by auto negotiating with data center level network switches
SNMP Compatibility	Yes
Network Compatibility	10 Mbps, 100 Mbps (Fast Ethernet), 1 Gbps (Gigabit)
Network Card	Panduit G5 Gigabit Network Module
Communications Interface	(1) RJ45 Network, (2) RJ45 Sensor, (2) RJ45 Daisy Chain, (1) USB

Specifications (continued)

Daisy-Chainable / Cascadable	Cascade up to 4 PDUs
LED Indicators	Green LED indicates outlet is on
Material	Metal
Finish/Coating	Powder-Coated
Color	Black
Overall Height (In.)	69
Overall Height (mm)	1750
Overall Width (In.)	3.3
Overall Width (mm)	85
Overall Depth (In.)	2.1
Overall Depth (mm)	53
Number of Rack Units	40
Maximum Operating Temperature (°C)	60
Maximum Operating Temperature (°F)	140
Minimum Operating Temperature (°C)	10
Minimum Operating Temperature (°F)	50
Maximum Storage Temperature (°C)	60
Maximum Storage Temperature (°F)	140
Minimum Storage Temperature (°C)	-20
Minimum Storage Temperature (°F)	-4
Compliance Certifications	RETIE (Colombia)
Standards Met	CE, UKCA, ROHS, REACH, China ROHS
Product Warranty Period (Worldwide)	3 years

Packaging Detail

UPC	61305631777
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	1.7026
Std. Ctn. Qty.	0
Std. Ctn. Volume (cf)	0.0000