## **Product datasheet**

Specification





# Easy UPS 3M 200kVA 400V 3:3 UPS for external batteries, Start-up 5x8

E3MUPS200KH

### Overview

Lead time Usually Ships within 6 Weeks

#### Main

Mairi		
Main Input Voltage	400 V 3 phases	
Other Input Voltage	380 V	
	415 V	
Main Output Voltage	400 V 3 phases	
Other Output Voltage	380 V	
	415 V	
Rated power in W	200 kW	
Rated power in VA	200 kVA	
Provided equipment	Dust filter	
	Installation guide	
	Start-up service	

### **Batteries & Runtime**

Efficiency	View Efficiency Graph ☐
Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	0

## **Physical**

Colour	White (RAL 9003)
Height	130 cm
Width	60 cm
Depth	85 cm
Net weight	304 kg
USB compatible	Vas

## Input

Maximum input current	336 A
Max short time withstand current	10 kA
Input harmonic distortion	Less than 3 % for full load
Load power factor	0.5 leading to 0.5 lagging without derating

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Input Power Factor at Full Load	0.99
Input voltage limits	342477 V
Network frequency	4070 Hz

## Output

Maximum configurable power in VA	200 kVA
Maximum configurable power in W	200 kW
Output frequency	50 Hz sync to mains 60 Hz sync to mains
Harmonic distortion	Less than 3 %
Output harmonic distortion	< 3% linear load and < 5% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Output voltage tolerance	+/- 1 %
UPS type	Double conversion online
Wave type	Sine wave

## **Environmental**

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	04921 ft
Ambient air temperature for storage	-2555 °C
Storage Relative Humidity	095 % non-condensing
Storage altitude	0.000000000015240.0000000000 m
Acoustic level	72 dBA
Heat dissipation	34121 Btu/h
IP degree of protection	IP20

## **Communications & Management**

Control panel Touch screen LCD user interface

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	150 cm
Package 1 Width	97.5 cm
Package 1 Length	72.5 cm
Package 1 Weight	338 kg

## **Contractual warranty**

Warranty 1 year on-site repair or replace with factory authorized Start-Up



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance



Mercury Free



Rohs Exemption Information

Yes

### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information