

4XEM's USB-C 45W Fast Charging 3.0 Wall Charger - Black

4XEM Part- 4XSAM45WPWRB



4XEM USB-C 45W fast charging Wall Charger is completely compatible with all USB powered devices. With high-speed charging, our 45W 3A USB Type C wall charger will supply the quick battery boost when you need it. Its sleek compact design makes it great for travel. Its design is also perfect for its wide variety of compatibility. 4XEM's USB C power block delivers a full 45W charging power via the USB-C female port in tandem with one of our many USB-C cables to juice up your mobile phone, tablets, or any USB powered devices. Our certified Fast Charging USB-C wall charger is designed with high quality material for strength and durability.

Problem it solves: 4XEM's USB-C 45W fast charging wall charger is an ideal partner any USB-C compatible device for a quick efficient charge whenever you need a boost!

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com



Features


- Support HiSilicon Fast Charging Protocol FCP、USB PD、BC、AFC etc for output
- voltage and current communication
- Accurate limited current output
- Over current protection with Auto-recovery.
- Overload protection and over voltage protection.
- Short circuit protection with Auto-recovery.
- Over temperature protection with Auto-recovery.
- Select precision electrical components, fire line version, and imported fire plastic.
- Portable and convenient to use
- Color: Black

Application

- Home
- Travel
- Charging
- Sync

**45W of
Fast Charging & Sync
Power**

Type-C USB Port



4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

**Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com**



**DATA SHEET**

Warranty Information	Warranty	1 year
Connector(s)	Charging Port Power	USB Type-C Direct Attached Non-Polarized NEMA 1-15P
Performance	Industry Standards	USB-PD 3.0 PPS Samsung Super Fast Charging 2.0 USB 3.1 Gen 2
Physical Characteristics	Charger Colour Display LED Indicator(s) Charger Width Charger Height Charger Length Charger Weight	Black No None 2.09 in [53.1 mm] 1.19 in [30.1 mm] 2.69 in [68.3 mm] 3.25 oz [92 g]
Power	Power Delivery Input Voltage Output Voltage (PD 3.0 - PDO) Output Voltage (PD 3.0 - PPS) Output Voltage (Other)	45W 100-240VAC, 50Hz-60Hz @ 0.7A 5V DC @ 3A 9V DC @ 3A 15V DC @ 3A 20V DC @ 2.25A 3.3V-11.0V DC @ 4.05A 3.3V-16.0V DC @ 2.8A 3.3V-21.0V DC @ 2.1A 5V DC @ 3A
Environmental	Operating Temperature Storage Temperature Humidity	0 to 40°C (32 to 104°F) -20 to 80°C (-4 to 176°F) 5% to 90% (non-condensing)
Packaging Information	Package Type Package Width Package Height Package Length Shipping (Package) Weight	Poly-bag 4.00 in [101.6 mm] 5.00 in [127.0 mm] 1.22 in [31.0 mm] 3.5 oz [99 g]
What's in the Box	Included in Package	45W USB-C Charger

* Product appearance and specifications are subject to change without notice.

* Same day shipping is only available for orders shipping within the United States.

4XEM Products Are Available At Your Favorite Online Retailers

WWW.4XEM.COM

Contact Todd Schaus 4XEM sales Rep
1-866-999-4936 Ext.104 tschaus@4xem.com

