

Overview

Business capabilities with up to 5,000 pages of pre-filled toner and an ultra-low cost per page[1]

Discover business-ready capabilities and savings with HP LaserJet Tank MFP 1602w All-in-One Printer pre-filled with up to 5,000 pages of Original HP Toner[1]

Get high-quality printing with ultra-low cost per page

Engineered for high-volume printing – prefilled with 5,000 pages of toner in the tank. [1]

Easy toner refill in 15 sec with Original HP Toner.

Easily refill Original HP Toner in 15 seconds. [5]

Full features for versatile productivity.

Maximize your uptime with print speeds up to 22ppm.

Features

| MFP performance | High yield HP Toner Reload Kit ^{1,3} |
|--|---|
| | |
| | |
| | |
| | |
| Self-reset dual band Wi-Fi ⁷ | HP Smart app ⁸ |
| | |
| | |
| | |
| Harana and the state of the sta | |
| Uncompromising laser quality | Up to 50,000-page imaging drum ⁶ |
| | |

[5] When used in accordance with instructions. Average reload time based on HP internal testing.

^[1] Actual yield varies considerably based on content of printed pages and other factors. Average based on ISO/IEC 19752 and continuous printing. Additional printed pages require toner reload. For details see www.hp.com/go/learnaboutsupplies.

Specifications

| Print Resolution Technologies | 600 x 400 dpi; 600 x 600 dpi |
|-----------------------------------|---|
| Print quality black (best) | Up to 600 x 600 dpi |
| Print speed black (ISO, A4) | Up to 22 ppm |
| Print speed black (ISO, letter) | Up to 23 ppm |
| Print speed | Print speed up to 22ppm (black, A4) |
| Functions | Print, copy, scan |
| Duplex printing | Manual (driver support provided) |
| Duty cycle (monthly, A4) | Up to 25,000 pages |
| Duty cycle (monthly, letter) | Up to 25,000 pages |
| Printer smart software features | HP Auto-On/Auto-Off, HP Smart App ^[1] |
| Energy savings feature technology | HP Auto-On/Auto-Off Technology; Instant-on Technology |
| Replacement cartridges | HP 154A Black LaserJet Tank Toner Reload Kit (Yield ~2500 pages); HP 154X Black LaserJet Tank Toner Reload Kit (Yield ~5000 pages); [3] |
| Supplies feature | HP LaserJet Tank Technology |
| Connectivity, standard | Hi-Speed USB (compatible with USB 2.0 specifications); 802.11a/b/g/n (2.4/5 GHz) Wi-Fi radio + BLE |
| Network capabilities | built-in WiFi 802.11b/g/n (2.4/5GHz) |
| Wireless capability | built-in WiFi 802.11b/g/n (2.4/5GHz) |
| Mobile printing capability | HP Smart App; Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing |
| Network protocols, supported | TCP/IP: IPv4; IPv6; LPD; SLP; Bonjour; WS-Discovery; BOOTP/DHCP/AutoIP; SNMP v 1/2/3;HTTP/HTTPS; UDP; IPP |
| Software included | No CD inbox (except Indonesia and China Gov) Downloadable Software from hp.com or 123.hp.com #CD include HP Software Installer, Uninstaller, printer driver and other essential tools |
| | Windows 11; Windows 10; Windows 7; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux |
| Compatible Operating Systems | (Not supporting Windows® XP (64-bit), Windows Vista® (64-bit) and Windows 8, 8.1. Full solution software available only for Windows 7 SP1, Windows 10 and newer; For Windows Server 2008 R2 64-bit, 2012 64-bit, 2012 R2 64-bit, 2016 64-bit only print driver is installed. Windows RT OS for Tablets (32 & 64-bit) uses a simplified HP print driver built into the RT OS; Linux systems use in-OS HPLIP software.) |
| Technical features | AirPrint; Compact size; HP Auto-On/Auto-Off; Scan-to-email; Wireless; Wireless Direct |
| Sustainable impact specifications | Recyclable through HP Planet Partners; Contains post-consumer recycled plastic |
| Energy star certified | No |
| Blue Angel compliant | Yes, Blue Angel DE-UZ 219—only ensured when using Original HP supplies |
| Copy speed black (normal, letter) | Up to 23 cpm |
| | |

| Scan file format | JPEG, RAW(BMP), PNG, TIFF, PDF |
|--------------------------------|--|
| Scan input modes | HP Smart App; and user applications via Twain |
| Scan technology | Contact Image Sensor (CIS) |
| Scanner type | Flatbed |
| Display area (imperial) | 0.94 x 0.94 in |
| Display area (metric) | 2.30 x 2.30 cm |
| Display | Icon LCD |
| Minimum dimensions (W x D x H) | 368 X 326 X 255 mm (Dimensions vary as per configuration) |
| Minimum dimensions (W x D x H) | 14.5 X 12.83 X 10 in (DImensions in shipping condition) |
| Weight | 7.9 kg (Weight varies as per configuration) |
| Weight | 17.4 lb (with P unit installed) |
| Power consumption | Active printing: 390w, Ready: 2.7w, Sleep: 0.51w, Manual Off: 0.05w, Auto Off/Manual On: 0.05w, Auto-Off/Wake on LAN: 0.5w (Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device.) |
| Power supply type | Internal (Built-in) power supply |
| What's in the box | HP Black Original LaserJet Tank Imaging Drum (introductory ~5000 page black toner yield provided, Power Cord, Setup Guide, Reference Guide, Regulatory/Support Flyers, CD (for APJ only) ^[2] |
| Manufacturer Warranty | One-year limited hardware warranty. For more info, please visit us at https://support.hp.com |

Additional specifications

| Acoustic power emissions (active, printing) | 6.3 B(A) |
|--|--|
| Acoustic power emissions (ready) | 2.6 B(A) |
| Acoustic pressure emissions bystander (active, printing) | 50 dB(A) |
| Acoustic pressure emissions bystander (ready) | 16 dB(A) |
| Automatic paper sensor | Yes |
| Bit depth | 24-bit |
| Bottom margin (A4) | 2 mm |
| Cable included | Yes, 1 USB Cable for 1602w. No USB Cable for 1604w |
| Cartons per layer | 8 |
| Certifications and compliances | RCM (Australia), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), BIS (India), KC (South Korea), SIRIM (Malaysia), Cambodia, Ukraine, EAC, Eastern European approvals, CE Marking, FCC, Energy Star, UL, Paraguay, Chile, Argentina, Indonesia, Singapore, Philippines, etc. |
| Color or black | Black and white |
| Color scanning | Yes |
| Compatible Network Operating Systems | Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux-imaging-and-printing) |
| Control panel | Icon LCD; 3 lights (Media, Wifi, Lid open); 10 buttons (WiFi, Down, Menu, Up, Copy, ID copy, Info, Resume, Cancel, Power) |
| Copy speed note | First Copy Out from Ready and Simplex Copy Speed measured using ISO/IEC 29183, Duplex Copy Speed measured using ISO/IEC 24735, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application and document complexity. |
| Count of layers in pallet | EMEA/APJ: 5; AMS: 6 |
| Country of origin | Made in Vietnam (WW except Brazil SKU) Made in Brazil (for Brazil SKU only) |
| Downloadable software | From 123.hp.com: HP Smart for Windows 11, 10, Mac, Mobile(Android and iOS); HP Easy Start for Windows 7; From hp.com: Full-solution software and drivers (with installer); HP Easy Start; Basic-solution software and drivers; Product Documentation and Support; HP Print and Scan Doctor; From Mobile OS: See "HP Mobile Printing" (http://http://www.hp.com/go/mobileprinting); From In-OS app stores: HP Smart; HP Print Service Plugin; From HP.com for printer administrators: Linux Print Drivers; HP Web JetAdmin Software (HP SNMP Proxy Agent) |
| Driver updates | Latest supported operating systems and Print drivers available at hp.com/support/ljtmfp160x |
| | |

| Duplex ADF scanning | No |
|--------------------------------------|---|
| Duty cycle note | Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups. |
| Electromagnetic compatibility | CISPR32:2015 & CISPR 35:2016 /EN55032:2015 - Class B; EN 61000-3-2:2019; EN 61000-3-3:2013+A1:2019; EN 55035:2017; FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 6 |
| Envelope Feeder | No specific envelope feeder. Envelope can be supported in Tray 1 |
| Finished output handling | 60 to 163 gram cut sheet paper |
| First copy out black (A4) | As fast as 11 sec |
| First copy out black (A4, sleep) | As fast as 11.5 sec |
| First copy out black (letter) | As fast as 10.5 sec |
| First copy out black (letter, sleep) | As fast as 11 sec |
| First page out black (A4, ready) | As fast as 8.0 sec |
| First page out black (A4, sleep) | As fast as 8.4 sec |
| First page out black (letter, ready) | As fast as 7.9 sec |
| First page out black (letter, sleep) | As fast as 8.3 sec |
| First page out footnote | [7] Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. |
| Input capacity | Up to 150 sheets |
| Left margin (A4) | 2 mm |
| Levels of grayscale | 256 |
| Mac compatible | Yes |
| Maximum Input Capacity (envelopes) | Up to 10 envelopes |
| Maximum Memory | 64 MB SDRAM |
| Maximum dimensions (W x D x H) | 368 X 390.5 X 255 mm |
| Maximum dimensions (W x D x H) | 14.5 X 15.4 X 10 in |
| Maximum input capacity (sheets) | Up to 150 sheets |
| Maximum metric depth | 390.5mm when Tray extended fully in operational state |
| Maximum metric height | 255mm when Tray extended fully in operational state |
| Maximum metric width | 368mm when Tray extended fully in operational state |
| Maximum output capacity (sheets) | Up to 100 sheets |
| Maximum print area | 215.9 x 355.6 mm |
| Media size, tray 1 | A6; A5; A4; Letter; No.10 Env; C5 Env; DL Env; B5(JIS); 105 x 148.5 mm to 215.9 x 355.6 mm; 216mm x 340mm |

| Media sizes supported | A6; A5; A4; No.10 Env; C5 Env; DL Env; B5 Env; B5(JIS); B6 (JIS); 216mm x 340mm; Custom |
|---|---|
| Media sizes supported | Letter; envelopes (No.10); Legal; Postcard; Double Postcard; Executive; Officio; Custom |
| Media sizes supported, key | 4 x 6 in; Letter; Legal; Envelopes |
| Media sizes supported, key | 10 x 15 cm; A4; Envelopes |
| Media sizes, custom | 4x 6 to 8.5 x 14 ln |
| Media sizes, custom | 102 x 152 to 215.9 x 355.6 mm |
| Media type and capacity, ADF | Standard printed media. 40 sheets Capacity. |
| Media type and capacity, tray 1 | Up to 150 sheets cut sheet or 10 envelope |
| Media types | Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope |
| Media weight (tray 1) | 60 to 163 g/m² |
| Media weight (tray 2) | NO tray 2 |
| Media weight (tray 3) | No Tray 3 |
| Media weight, supported | 60 to 163 g/m² |
| Media weight, supported | 16 to 43 lb |
| Memory | 64 MB |
| Metric depth | 326mm in shipping state |
| Metric height | 255mm in shipping state |
| Metric width | 368mm in shipping state |
| Minimum System Requirements | Microsoft® Windows® 11, 10, 7 SP1: 32-bit or 64-bit, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. |
| Minimum System Requirements for Macintosh | Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB HD; Internet required |
| Mobile printing capability footnote | [4] Wi-Fi Direct® footnote: Mobile device needs to be connected to Wi-Fi Direct® signal of a Wi-Fi Direct-supported AiO or printer prior to printing. Details at hp.com/go/mobileprinting. Wi-Fi Direct® is a registered trademark of Wi-Fi Alliance®. ^[4] |
| Native scan file format | JPG; PDF |
| Number of print cartridges | 1 (black) |
| Number of users | 1-5 Users |
| Operating humidity range | 10 to 80 %RH |
| Operating temperature range | 15 to 32.5℃ |
| Operating temperature range | 59 to 90.5°F |
| Output capacity | Up to 100 sheets |
| Package dimensions (W x D x H) | 17.01x 13.03 x 15.28 in |
| Package dimensions (W x D x H) | 432 x 331 x 388 mm |
| Package weight | 9.8 kg |
| | |

| Package weight | 21.6 lb |
|---|---|
| Page yield (set-up/inbox cartridges) | ~5,000 black pages |
| Pallet dimensions | EMEA/APJ: 47.24 x 39.37 x 82.32 in; AMS: 47.24 x 39.37 x 97.60 in |
| Pallet dimensions (W x D x H) | EMEA/APJ: 1200 x 1000 x 2091 mm; AMS: 1200 x 1000 x 2479 mm |
| Pallet weight | EMEA/APJ: 412.5 kg: AMS: 490.9 kg |
| Pallet weight | EMEA/APJ: 909.45 lb; AMS: 1082.2 lb |
| Paper handling input, optional | envelope and labels |
| Paper handling input, standard | 150 sheet input tray |
| Paper handling output, optional | envelope and labels |
| Paper handling output, standard | 100 sheet output |
| Paper trays, maximum | 1 |
| Paper trays, standard | 1 |
| Power | Printer-110V- RMN: L12543A; Rated Voltage: 110-127V; Rated Current: 5.2A; Frequency: 50/60Hz. Printer-220V- RMN: L12543E; Rated Voltage: 220-240V; Rated Current: 2.9A; Frequency: 50/60Hz |
| Print Technology | Laser |
| Print colors | No |
| Print languages | PCLmS; URF; PWG |
| Print quality black (normal) | Up to 600 x 400 dpi |
| Print resolution black (fine lines) | Up to 600 x 600 dpi |
| Print speed black (Landscape, A5) | Up to 23 ppm |
| Print speed black (Portrait, A5) | Up to 4 ppm |
| Print speed footnote (A5) | [5] Measured using ISO/IEC 24734 Feature Performance Test, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. |
| Print technology | Laser |
| Printer Management | HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) |
| Printer smart software features footnote | [1] HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade. [2]Requires the HP Smart app download. For details on local printing requirements see www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in all countries. See details: HPSmart.com at Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores. |
| Processor speed | 500 MHz |
| Product long name specifications | HP LaserJet Tank MFP 1602w; 5,000 inbox yield; Up to 22/23 ppm (A4/Letter); Up to 20,000 pages per month duty cycle; USB and Wireless |

| Product short name specifications | HP LaserJet Tank MFP 1602w Printer, Black and white, Printer for Business, Print, copy, scan, Scan to email; Scan to PDF |
|---|--|
| Quantity per pallet | EMEA/APJ: 40; AMS: 48 |
| RMN number | SHNGC-2101-01 |
| Recommended media weight (duplex) | No Duplex Support |
| Recommended media weight (duplex) | No Duplex support |
| Recommended monthly page volume | 250-2500 |
| Recommended monthly page volume note | HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period. |
| Recommended monthly scan volume | 150 to 1500 |
| Recommended monthly scan volume note | HP recommends that the number of scan pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period. |
| Recommended operating humidity range | 30 to 70% RH |
| Recommended operating temperature range | 17.5 to 25℃ |
| Recommended operating temperature range | 63 to 77°F |
| Replacement cartridges footnote | [3] Declared yields based on ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/toneryield |
| Resolution | Up to 600 dpi optical sensor |
| Right margin (A4) | 2 mm |
| Safety | IEC 60950-1:2005 +A1:2009+A2:2013; IEC/EN 62368-1:2014; CAN/CSA C22.2 No. 62368-1, 3rd Edition; UL62368-1, 3rd Edition; IEC 60825-1 3rd Edition (Class 1 Laser Product); EN 62479:2010 / IEC 62479:2010; Compliance of IEC 60950-1 standard considers all country deviations according to the most recent IECEE CB Bulletin; Complies with FDA performance standards for laser products except for conformance with IEC 60825-1 Ed.3.,as described in Laser Notice No. 56, dated May 8, 2019 |
| Scan resolution, hardware | 600 x 1200 dpi |
| Scan resolution, optical | Up to 600 dpi |
| Scan size, maximum | 216 x 297 mm |
| Scan size, maximum | 8.5 x 11.7 in |

| Security management | Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default, Cipher & TLS selection; Account lockout; Secure Wi-Fi setup |
|--|---|
| Segment (filter) | Business |
| Software scan file format | JPEG, RAW(BMP), PNG, TIFF, PDF |
| Standard output capacity (envelopes) | Up to 10 envelope |
| Standard output capacity (transparencies) | No transparency support |
| Storage temperature range | -20 to 60°C |
| Storage temperature range | -4 to 140°F |
| Target user and print volume | For teams up to 5 users; Prints up to 2,500 pages/month |
| Tariff numbers | (AM) 8443310000; (EU) 8443310000; (AP) 84433129 |
| Telecom compliance (fax capability) | Wireless: EU RED 2014/53/EU; ETSI EN 301 489-1 V2.2.3 / ETSI EN 301 489-17: V3.1.1; EN 300 328: V2.2.2 / EN301 893 V2.1.1 / EN300 440-1 V2.1.1; FCC Title 47 CFR, Part 15 Subpart C & E / RSS 247 Issue 1, 2015 & RSS 102 Issue 5, 2015; IEC 62311:2007 / EN62311:2008 |
| Top key features | Scan to email; Scan to PDF |
| Top margin (A4) | 2 mm |
| Twain version | Version 2.1 |
| Typical electricity consumption (TEC) footnote | [8] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device. |
| Typical electricity consumption (TEC) number | Energy Star: 0.194Kwh/week; Blue Angel: 0.203Kwh/week ^[8] |
| UNSPSC code | 43212110 |
| UPC number | (696) 196188154120; (AC8) 195908728825; (ACQ) 195908728832; (AKV) 195908728849; (B13) 195908728856; (B19) 195908728863; (BBU) 195908728870; (BGJ) 195908728887 |
| Warm-up time | As fast as 20 sec |
| What is in the box footnote | [2] HP Black Original LaserJet Tank Imaging Drum (introductory ~5,000 page black toner yield provided). For yield information included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. |

[1] HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade. [2]Requires the HP Smart app download. For details on local printing requirements see www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in

all countries. See details: HPSmart.com at Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores.

- [2] HP Black Original LaserJet Tank Imaging Drum (introductory ~5,000 page black toner yield provided). For yield information included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.
- [3] Declared yields based on ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/toneryield
- [4] Wi-Fi Direct® footnote: Mobile device needs to be connected to Wi-Fi Direct® signal of a Wi-Fi Directsupported AiO or printer prior to printing. Details at hp.com/go/mobileprinting. Wi-Fi Direct® is a registered trademark of Wi-Fi Alliance®.
- [8] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.

Ink/Toner/Paper/Printer Supplies

HP Laser Toner Cartridges and Kits

HP Black and White Laser Toner Reload Kits

| HP 153A Black Original LaserJet Tank Toner Reload Kit | W1530A |
|---|--------|
| HP 153X Black Original LaserJet Tank Toner Reload Kit | W1530X |
| HP 154A Black Original LaserJet Tank Toner Reload Kit | W1540A |
| HP 154X Black Original LaserJet Tank Toner Reload Kit | W1540X |
| HP 158A Black Original LaserJet Tank Toner Reload Kit | W1580A |
| HP 158X Black Original LaserJet Tank Toner Reload Kit | W1580X |

★: Recommended

Disclaimer — Copyright

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Nov 18, 2022 11:50 PM UTC+0000