APC Smart-UPS Online Lithium ion XBP 180V 2U Rack/Tower



SRTL180RM2UBP

Uν	er	VI	е	W
----	----	----	---	---

Lead time Usually in Stock

Main

Number of rack unit 2U

Provided Equipment Rack Mounting brackets Vertical mounting brackets

Batteries & Runtime

Battery Slots Empty 0 0 **Included Battery Modules Battery voltage** 180 V Replacement battery SRYLBM [7

Physical

Color Silver grey Height 3.39 in (86 mm) Width 17.01 in (432 mm) Depth 28.50 in (724 mm) **Net Weight** 71.43 lb(US) (32.4 kg) **Mounting Mode** Rack-mounted with kit Tower-mounted with kit

Conformance

Product Certifications UL 1973

Environmental

Ambient air temperature for 32...104 °F (0...40 °C) operation Operating altitude 0...10000 ft **Relative Humidity** 0...95 % non-condensing 5...113 °F (-15...45 °C) **Ambient Air Temperature for** Storage

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage altitude	050000 ft (0.0015240.00 m)
Storage Relative Humidity	095 % non-condensing

Ordering and shipping details

GTIN 731304437024

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	4
Package 1 Height	15.43 in (39.2 cm)
Package 1 Width	23.03 in (58.5 cm)
Package 1 Length	38.74 in (98.4 cm)
Package 1 Weight	92.59 lb(US) (42 kg)
SCC14	10731304437024

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
RoHS exemption information	Yes	

Contractual warranty

Warranty 5 years

Recommended replacement(s)