



TS-932PX-4G

CPU	AnnapurnaLabs Alpine AL324 ARM® Cortex-A57 quad-core 1.7GHz processor
CPU Architecture	64-bit ARM
Maximum Memory	16 GB (1 x 16 GB)
Memory Slot	1 x SO-DIMM DDR4
Flash Memory	512 MB (Dual boot OS protection)
Drive Bay	5x 3.5-inch+ 4 x 2.5-inch SATA 6Gb/s
Drive Compatibility	<p>3.5-inch bays:</p> <ul style="list-style-type: none"> 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives <p>2.5-inch bays:</p> <ul style="list-style-type: none"> 2.5-inch solid state drives
Hot-swappable	Yes
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2 (also support 10M)
10 Gigabit Ethernet Port	2 x 10GbE SFP+
Wake on LAN (WOL)	Yes
Floating Point Unit	Yes
Encryption Engine	Yes
System Memory	4 GB SODIMM DDR4 (1 x 4 GB)
Jumbo Frame	Yes
USB 3.2 Gen 1 port	3
Form Factor	Tower
LED Indicators	System Status, LAN, USB, HDD1~5, SSD1-4
Buttons	Power, Reset, USB Copy
Dimensions (HxWxD)	182.7 × 224.6 × 224.1 mm

Weight (Net)	3.39 kg
Weight (Gross)	4.99 kg
Operating temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Supply Unit	External, 120 W, AC 100 to 240 V
Fan	1 x 140mm, 12VDC
Sound Level	18.6 db(A)
System Warning	Voice prompts or Buzzer
Kensington Security Slot	Yes

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.