

## OVERVIEW

Upgradeable Switched Unit Level Monitored EC rPDUs provide reliable power distribution to critical IT equipment while delivering individual outlet level control and a comprehensive view of input power usage via remote network access. Includes environmental monitoring capabilities to obtain real-time environmental metrics. Upgrade the hot-swappable monitoring device on select units to leverage new technologies and accommodate changing business needs.

### Benefits

- Remotely reboot outlets to power cycle unresponsive IT equipment or increase runtime of critical equipment upon power failure with outlet-level control.
- Reliable power distribution with local and remote power monitoring options offer quick access to critical power usage information to evaluate energy usage trends and maximize uptime.
- Environmental monitoring capabilities with the addition of optional environmental sensors ensure users have critical infrastructure data at their fingertips to prevent climate-related equipment failure and system downtime.
- Fault-Tolerant Daisy Chaining with RSTP simplifies intelligent rPDU connectivity and ensures data is reported even when a break in the network chain occurs. Supports up to 40 rPDUs.
- Daisy-chain up to 50 devices on a single IP address and reduce



## Part #: VP5N62A1

**Model Number:** MNS5MDR6-12CF18-6PS15D0H10-S

**Category:** Switched

**Sub Category:** Unit Level Monitoring

**Power Configuration:** 60A, 208V DELTA, 17.2kW

**Physical Configuration:** 19in / 483mm, Horizontal

### Product Summary:

rPDU, Switched Unit Level Monitoring EC, 60A, 208V DELTA, 17.2kW, Horizontal, (12) Combination C13/C19, 10ft / 3m power cord with 3P+E (IP67), Black Powder Coat.

### Monitoring:

Input power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display.

### Plug Form:



3P+E (IP67)

### Receptacle:



Combination C13/C19  
(Quantity: 12)

### Chassis Color Options:

deployment time with self-configuration of downstream devices.



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

|                                         |                                                                                                                                                                                                                                        |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Monitoring                              | Input power monitoring with Outlet switching. Circuit/Breaker current monitoring. Environmental monitoring via optional remote sensors. Daisy chain Ethernet connectivity. Local high visibility LED display.                          |
| Input Monitoring                        | Total Unit Monitoring (kWh, W, VA, PF)<br>Phase (AB, BC, CA) Monitoring (kWh, W, VA, PF, V, A)<br>Line (A, B, C) Monitoring (A)<br><br>Power Measurements Compliant with ANSI C12.1 and IEC 62053-21 at 1% Accuracy Class Requirements |
| Circuit Monitoring                      | Circuit / Breaker Monitoring (A)<br><br>Circuit/Breaker Current Measurements Independently Tested and Verified at 2% Accuracy                                                                                                          |
| Remote Power Management                 | Individual Outlet Switching with Optional User Defined Time Delays and Sequential Power-up                                                                                                                                             |
| Quantity Of Inputs                      | 1                                                                                                                                                                                                                                      |
| Voltage                                 | 200-240V Delta                                                                                                                                                                                                                         |
| Current                                 | 60A x 3 Phase DELTA                                                                                                                                                                                                                    |
| VA per Input (Load Capacity)            | 17.2kW (208V)                                                                                                                                                                                                                          |
| Frequency                               | 50/60Hz                                                                                                                                                                                                                                |
| Over Current Protection                 | (6) 20A Double Pole Magnetic Breakers (10kAIC Rated)                                                                                                                                                                                   |
| Switch                                  | Breaker/Switch Combination                                                                                                                                                                                                             |
| LCD Touchscreen Display / Auto Oriented | Yes                                                                                                                                                                                                                                    |
| Indicators - LED(s)                     | 12                                                                                                                                                                                                                                     |
| Power Cable Wire Gauge                  | 6/4                                                                                                                                                                                                                                    |
| Power Cable Length                      | 10ft / 3m                                                                                                                                                                                                                              |
| Power Entry Location                    | Left Rear                                                                                                                                                                                                                              |
| Plug Type                               | IEC60309 3P + E, 60A, Watertight IP67                                                                                                                                                                                                  |
| Receptacle/Socket Type #1               | Combination C13/C19                                                                                                                                                                                                                    |
| - Quantity on Rear                      | 12                                                                                                                                                                                                                                     |
| - Quantity per Breaker                  | 2                                                                                                                                                                                                                                      |
| - Quantity per Phase Combination        | 4                                                                                                                                                                                                                                      |
| - Circuit Color ID                      | 6 Circuit = Orange, Green, Blue, Light Orange, Light Green, Light Blue                                                                                                                                                                 |
| - Style                                 | Banks of 6                                                                                                                                                                                                                             |
| - Voltage per Receptacle/Socket         | 208V                                                                                                                                                                                                                                   |
| Network Connection                      | Dual 10/100/1000Mbps Ethernet                                                                                                                                                                                                          |
| Protocols Supported                     | DHCP, HTTP, HTTPS, IPv4, IPv6, LDAP, NTP, RADIUS, RSTP, SSH, SMTP, SNMP (v1/v2c/v3), Syslog, TACACS+, Modbus TCP                                                                                                                       |
| Data Access Formats                     | CSV datalog, JSON API, JSON datalog                                                                                                                                                                                                    |
| USB Support                             | Yes                                                                                                                                                                                                                                    |

|                                   |                                                                                                           |
|-----------------------------------|-----------------------------------------------------------------------------------------------------------|
| IP Reset Button                   | Yes                                                                                                       |
| Hard Reboot Button                | Yes                                                                                                       |
| Serial Connection                 | RS232 via RJ45                                                                                            |
| Remote Sensor RJ Connection Jacks | 1 (Supports up to 16 Sensors)                                                                             |
| Maximum Operating Temperature     | 60C / 140F                                                                                                |
| Heavy Steel - Powder Coat Finish  | Black                                                                                                     |
| Configuration                     | 2U                                                                                                        |
| 19in Recess Mount                 | Yes                                                                                                       |
| Country of Origin                 | USA, TAA Compliant and Buy American Act COTS Compliant                                                    |
| Product Warranty                  | 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years |
| Certification/Agency Approvals    | RoHS Compliant                                                                                            |
| Certification/Agency Approvals    | FCC Part 15 Class A Conformance                                                                           |
| Certification/Agency Approvals    | UL & c-UL Listed 62368-1                                                                                  |
| Chassis Dimensions (HxWxD)        | 3.39in x 17in x 12in / 87mm x 432mm x 305mm                                                               |
| Shipped Weight                    | 20lbs (9.07kg)                                                                                            |